

CARDIOLOGY STETHOSCOPES

- 32550 CARDIOLOGY CLASSIC STETHOSCOPE - blue
 - 32551 CARDIOLOGY CLASSIC STETHOSCOPE - burgundy
 - 32552 CARDIOLOGY CLASSIC STETHOSCOPE - black
- Cardiology Classic offers acoustical excellence in a traditional design with superior durability. Its innovative features include:
- stainless steel chestpiece (diameter 33-44 mm) with extra deep cone-shaped bell for a superb low frequency response
 - stainless steel double inner spring binaural
 - ultra-sensitive diaphragm for unsurpassed amplification
 - durable, elegantly moulded 55.5 cm (22") PVC tubing (int. Ø 6.5 mm, ext. Ø 12 mm)
- Manual and box in 11 languages: GB, FR, DE, IT, ES, PT, GR, PL, HU, SE, Arabic.



It comes in a foam lined box with 2 extra set of PVC eartips

- 32678 DIAPHRAGM Ø 44 mm - spare

Colour coordinated non-chill ring and diaphragm retaining ring, PVC tubing



32552

PROFESSIONAL STETHOSCOPE

- 32526 REGALITE - black
- Top quality single head stethoscope. Patented multi-frequency "ring-o-raised™" diaphragm system. Chromed plated chestpiece with "SUPERFLEX" inner spring binaural and 1 piece moulded, latex free, PVC tubing. Supplied in deluxe box, with spare soft eartips and one spare diaphragm. Manual and box in 7 languages: GB, FR, IT, ES, PT, GR, Arabic.



32526

LYNX MULTI-FUNCTIONAL VISUAL STETHOSCOPE

- 32596 LYNX MULTI-FUNCTION STETHOSCOPE with SpO₂ probe, USB cable and adapter
 - 32598 SpO₂ PROBE - spare
- Multi-function visual stethoscope with real time display of ECG waveform, heart rate and pulse oximeter.
- compact and portable, easy to use
 - adjustable screen contrast
 - adult SpO₂ sensor
 - alarm function for SpO₂ and Pulse rate
 - low power consumption
- Multilanguage box and manual: GB, FR, IT, ES



32596

TECHNICAL SPECIFICATIONS

Heart rate	Measurement range: 30 - 300 bpm	SpO₂	Measurement range: 0% - 100%
	Accuracy: ±2 bpm		Accuracy: 70% - 100% ±2%, <70% unspecified
Pulse rate	Measurement range: 30 - 250 bpm	Other	Power supply: Rechargeable lithium battery DC 3.7 V
	Accuracy: ±2 bpm or ±2% (select larger)		Display: 2.7" LCD
			Size: 87x63x19 mm

MULTI-FUNCTIONAL VISUAL STETHOSCOPE

- 32597 MULTI-FUNCTION VISUAL STETHOSCOPE with SpO₂ probe, USB cable and adapter, earphone
 - 32598 SpO₂ PROBE - spare
- The device includes stethoscope function and displays ECG waveform, heart rate, SpO₂, pulse and pulse waveform. Suitable for hospital, clinic, medical community and family.
- compact, light and portable, easy to use
 - earphone output and adjustable volume
 - alarm for SpO₂ and pulse rate exceeding limits
 - real-time detecting, data storage and review
 - real-time clock
 - recorded data can be transferred to PC
 - PC analysis software
 - low power consumption
- Multilanguage box and manual: GB, FR, IT, ES



CE 0123

32597



TECHNICAL SPECIFICATIONS

Stethoscope	Heart: 20 - 230 Hz	Pulse rate	Measuring range: 30 - 250 bpm	Other	Battery: 3.7 V rechargeable lithium battery
	Lung: 100 - 800 Hz		Accuracy: ±2 bpm or ±2% (select larger)		Display: 2.4" colour TFT
	H&L: 20 - 800 Hz	SpO₂	Measuring range: 0% - 100%		Size: 110x60x14 mm
	Heart rate		Accuracy: 70 - 100% (±2%) <70% unspecified		
	Measuring range: 30 - 300 bpm				
	Accuracy: ±2 bpm				